

Model HA/PA31

Michelangelo Series

Powered by Interpump Group



MODEL TABLE* | MAXIMUM CAPACITY (l/h)** LINKED TO THE RELATED PRESSURE (bar)

MODELS	POWER kW	PRESSURE bar	150	200	250	400	600	1000	1200	1500
HA/PA31015	15	CAPACITY l/h	2.400	2.000	1.500	800	600	300	200	200*

*Values referring to machines with fixed capacity

**Values referring to products with a max viscosity of 500Cp


TECHNICAL DATA

Plunger number	3
Stroke (mm)	50
Weight (Kg)	650
Water consumption (l/h)	150
Lubrication oil quantity (kg)	(SAE 85W-90) 4
Air and water inlet	1" female
Water discharge	½ female
Product inlet/outlet	Socket weld flange \varnothing e40 \varnothing i37 / \varnothing e29 \varnothing i22

Design according to MACHINE DIRECTIVES and the HARMONIZED EUROPEAN STANDARD in force.



Model HA/PA31



FEATURES

Forged block made of Duplex, SAF2205, 3 Plungers made of AISI630L

Direct transmission system with trapezoidal belts and pulleys

Homogenizing group with hydro-pneumatic adjustment of the pressure for a great stability and homogenizing valves in stellite™

Flat valve seat and poppet/ball valves type made of stellite 20™

Digital pressure transmitter, 4-20 mA, with ceramic membrane

Overpressure valve, flow switch alarm

Splash lubrication system, die cast aluminium crankcase, nitrurized crankshaft

Terminal box and control panel for local/remote control

Easy opening panels

OPTIONS

Second stage homogenizing group

Forged multi-block made of Super Duplex, SAF2507

Aseptic execution

- Sterile water generator by means of condensed steam generator
- Patent pending sterile water generator by means of microfiltration

Design suitable with: 3A, EHEDG or PHARMA

- Low roughness and electropolished wetted parts
- Certification manual for cGMP

Standard or Sharp Edge Homogenizing valve with different geometries, materials availability:

- Tungsten carbide
- Zirconia Oxide

Seat valve made of Tungstene carbide

Vibration and temperature monitoring and alarm

Pumping plungers availability:

- HVOF chromium carbide jet coat treatment
- AL2O3, Integral ceramics

Electric power board

- for Fixed or Variable capacity
- Remote Control by 4-20 mA signal
- Fully Automatic pressure control by means of PLC

Inlet and outlet connections

- DIN 11851, Tri Clamp, SMS
- High pressure outlet
- Option upon request

Explosion proof design

Soundproof design

***Technical specifications are not mandatory and subject to change without notice.

REV12-01/2021EN

